



Chester Milling Machine

- 3-Axis Power Feed
- Large Table Area
- Compact Design
- Universal Head
- Horizontal Milling
- Swivel Table

STANDARD ACCESSORIES

- ✓ 3-Axis DRO
- ✓ 3-Axis Power feed
- ✓ Work Lamp
- ✓ Coolant System
- ✓ Table Guard
- ✓ Manual & Parts List
- ✓ Toolbox

OPTIONAL ACCESSORIES

- Standard Swivel Base Vice
- Super Open Milling Vice
- Clamp Kit
- Dividing Head
- Rotary Table
- Dividing Plates
- Drill chuck
- 3 Jaw Chuck for Dividing Head
- Milling Collet Chuck Set
- Boring Head
- Reducing Sleeve Set
- Long Milling Arbors



Table	
Working Surface	1270x320mm
T-Slots, Number and Size	3/14mm
T-Slots Centres	70mm
Longitudinal Travel	730mm
Cross Travel	290mm
Vertical Travel	380mm
Load Capacity	200kg
Table Swivel Degree	45°
Spindle (Vertical)	
Spindle Taper	ISO40
Number of Speeds	8
Speed Range	90-2000rpm
Spindle Centre to Column	220mm-560mm
Spindle to Table	120-500mm
Quill Travel	120mm
Drawbar	M16
Milling and Drilling Capacity in Steel (S235JR) - Vertical	
End Milling Capacity	100mm
Vertical Milling Capacity	25mm
Tapping Capacity	16
Drilling Capacity	30mm
Spindle (Horizontal)	
Spindle Taper	ISO40
Number of Speeds	12
Speed Range	60-1350rpm
Quill Travel	120
Spindle to Table	10-340mm
Drawbar	Standard

Milling and Drilling Capacity in Steel (S235JR) - Horizontal	
End Milling Capacity	100mm
Horizontal Milling Capacity	100mm
Tapping Capacity	n/a
Drilling Capacity	n/a
Feed Rates	
Number of Feeds	8
Longitudinal	20-800mm/min
Cross	20-800mm/min
Vertical	10-400mm/min
Rapids Longitudinal	1000mm/min
Rapid Cross	1000mm/min
Rapid Vertical	500mm/min
Power	
Spindle Drive Motor	2.2kw(2.95hp)
Feed Motor	0.75kw(1.005hp)
Coolant Motor	0.04kw(0.05hp)
Weight and Dimensions	
Overall Dimensions (L x W x D)	1680x1640x-2200mm
Net Weight	1650kg

* The above specifications are subject to change without prior notice, no liability for mistakes. Machines may be shown with optional equipment.