



Features:

- Geared Head
- Wide Speed Range
- Cast Iron Construction

Standard Accessories:

- Drill Chuck and Arbor
- Manual and Parts List
- Morse Taper Sleeves
- Foundation Bolts

Model	BD25G Super	FD25G Super
Drilling Capacity (Mild Steel)	26mm	26mm
Drilling Capacity (Cast Iron)	26mm	26mm
Tapping Capacity (Mild Steel)	M10	M10
Tapping Capacity (Cast Iron)	M16	M16
Spindle Taper	MT3	MT3
Distance from Spindle to Column	max 255mm	max 255mm
Distance from Spindle to Table (min/max)	n/a	max 840mm
Distance from Spindle to Base (min/max)	20/535mm	950/1250mm
Rotation of Table along with column	n/a	n/a
Tilting Angle of Drilling Head	n/a	n/a
Vertical Travel of Drilling Head	535mm	320mm
Tilting Angle of Table	n/a	n/a
Vertical Travel of Table	n/a	510mm
Table Size	n/a	500x350mm
Number and size of T slots on Table	n/a	14x25x13mm
Feeds and Spindle	n/a	140mm
Maximum Spindle Traverse (hand/power)	125mm	125mm
Number of Spindle Speeds	8	8
Range of Spindle Speeds	105,210,350,445,700,890,1450,2900rpm	105,210,350,445,700,890,1450,2900rpm
Base Size Overall	570 x 340mm	500 x 400mm
Base Working Surface	570 x 340mm	500 x 400mm
Number and Size of T Slots on Base	2, 14 x 28 x 10mm	n/a
Distance between T Slots	130mm	n/a
Column Diameter	100mm	100mm
Main Motor Power	0.9/1.1kW (1.2/1.47hp)	0.9/1.1kW (1.2/1.47hp)
Weight and Dimensions		
Overall Height	1050mm	1750mm
Net Weight	155kg	192kg
Case Dimensions	570 x 340 x 1050mm	500 x 400 x 1750mm

* The above specifications are subject to change without prior notice, no liability for mistakes. Machines may be shown with optional equipment.