



Features:

- D.C. Injection Brake
- T Slotted Box Table
- Coolant System
- Low-Volt Work Light
- Hydraulic Gear Selection
- Ground and Hardened Guideways
- Arm Elevation via Screw and Motor
- Full Hydraulic Clamping

Model	G63 x 2000
Drilling Mild Steel	63mm
Drilling Cast Iron	80mm
Tapping Mild Steel	M30
Tapping Cast Iron	M36
Spindle Taper	MT5
Distance from Spindle to Column (min/max)	450-2000mm
Distance from Spindle to Base (min/max)	400-1600mm
Rotation Arm around Column	±180°
Vertical Travel of Arm	800mm
Size of Box Table	800 x 630 x 500mm
Number and Size of T Slots on Table	7/22mm
Distance between T Slots	150mm
Maximum Spindle Traverse (hand/power)	400mm
Number of Spindle Speeds	16
Range of Spindle Speeds	20-1600rpm
Number of Feed Rates	16
Range of Power Feed Rates	0.04-3.2mm/r
Base Size Overall	2900 x 1250mm
Base Working Surface	2100 x 1090mm
Number and Size of T Slots on Base	4/28mm
Distance between T Slots	250mm
Column Diameter	450mm
Main Motor Power	5.5kW (7.37hp)
Coolant Pump Motor	0.125kW (0.17hp)
Table Elevation Motor	1.5kW (2hp)
Clamping/Hydraulic Motor	0.75kW (1hp)
Overall Height	3205mm
Footprint (L x W)	3080 x 1250mm
Net Weight	7000kg

Standard Accessories:

- Work Light
- Coolant System
- Box Work Table
- Fixing Bolts
- Reducing Sleeves
- D.C. Brake
- Manual and Parts List

* The above specifications are subject to change without prior notice, no liability for mistakes. Machines may be shown with optional equipment.