



Features:

- D.C. Injection Brake
- T Slotted Box Table
- Coolant System
- Low-Volt Work Light
- Hydraulic Gear Selection
- Ground and Hardened Guideways
- Arm Elevation via Screw and Motor
- Full Hydraulic Clamping

Model	G80 x 2500
Drilling Mild Steel	80mm
Drilling Cast Iron	100mm
Tapping Mild Steel	M36
Tapping Cast Iron	M40
Spindle Taper	MT6
Distance from Spindle to Column (min/max)	500-2500mm
Distance from Spindle to Base (min/max)	550-2000mm
Rotation Arm around Column	±180°
Vertical Travel of Arm	1450mm
Size of Box Table	1000 x 800 x 560mm
Number and Size of T Slots on Table	7/22mm
Distance between T Slots	150mm
Maximum Spindle Traverse (hand/power)	450mm
Number of Spindle Speeds	16
Range of Spindle Speeds	16-1250rpm
Number of Feed Rates	16
Range of Power Feed Rates	0.04-3.2mm/r
Base Size Overall	3530 x 1400mm
Base Working Surface	2455 x 1220mm
Number and Size of T Slots on Base	4/28mm
Distance between T Slots	276mm
Column Diameter	550mm
Main Motor Power	7.5kW (10.05hp)
Coolant Pump Motor	0.125kW (0.17hp)
Table Elevation Motor	3kW (4hp)
Clamping/Hydraulic Motor	0.75kW (1hp)
Overall Height	3825mm
Footprint (L x W)	3730 x 1400mm
Net Weight	11000kg

Standard Accessories:

- Work Light
- Coolant System
- Box Work Table
- Fixing Bolts
- Reducing Sleeves
- D.C. Brake
- Manual and Parts List

* The above specifications are subject to change without prior notice, no liability for mistakes. Machines may be shown with optional equipment.