



Chester Drilling Machines




PRO17 - 25VS



Cast Aluminium Quill Depth Bracket



Variable Speed Change Lever



PRO25-17VS Belt Drive System



PRO18 - 25VS



PRO25-18VS Belt Drive System



Variable Speed Change Lever

Model	PRO17 - 25VS	PRO18 - 25VS
Drilling Capacity (Mild Steel)	25mm	25mm
Drilling Capacity (Cast Iron)	25mm	25mm
Tapping Capacity (Mild Steel)	MT3	MT3
Tapping Capacity (Cast Iron)	MT3	MT3
Spindle Taper	MT3	MT3
Distance from Spindle to Column	216mm	230mm
Distance from Spindle to Table(min/max)	130-800mm	160-670mm
Distance from Spindle to Base(min/max)	1240mm	1160mm
Rotation of Table along with column	360°	360°
Tilting Angle of Table	45°-45°	45°-45°
Vertical Travel of Table	670mm	510mm
Table Size	345x345mm	405x320mm
Number and size of T slots on Table	4-16X125mm	2-14X335mm
Distance between T Slots	90°	98
Maximum Spindle Traverse(hand/power)	80mm	120mm
Number of Spindle Speeds	step less	step less
Range of Spindle Speeds	280-2600rpm	85-1900rpm
Number of Feed Rates	1 or 3	3
Power Feed Rates	50hz	50hz
Base Size Overall	520X320mm	550x370mm
Base Working Surface	240X280mm	370X345mm
Number and Size of T Slots on Base	2/15X175mm	2/16X320mm
Distance between T Slots	160mm	120mm
Column Diameter	80mm	100mm
Main Motor Power	1kw(1.33hp)	1.5kw(2hp)
Overall Height	1700mm	1800mm
Net Weight	100kg	274kg
Case Dimensions	520x320x1700mm	570x395x1800mm

- Variable Speed
- Built in Lamp
- Heavy Duty Cast Iron Construction
- Simple To Operate

STANDARD ACCESSORIES

- Keyless Drill Chuck and Arbor
- Chuck Guard
- N.V.R. Switch gear
- Manual and Parts List

* The above specifications are subject to change without prior notice, no liability for mistakes. Machines may be shown with optional equipment.