



Chester Ring Rollers • RR Series

**RR40**

Model	RR40	RR50	RR65
Dia. Of Roller	40mm	50mm	65mm
Power	1.5kw (2hp)	2.2kw (3hp)	2.25kw (3hp)
Spindle Speed	9.3r/min	13r/min	9.3r/min
Dimensions	1270x890x1580mm	1000x8200x1550mm	1250x1150x1800mm

**RR50**

Model	RR40		RR50		RR65	
Capacity	Size	Min Dia.	Size	Min Dia.	Size	Min Dia.
	50x10mm 20x6mm	600mm 800mm	60x10mm 40x10mm	500mm 650mm	80x25mm 40x10mm	600mm 500mm
	60x20mm 30x6mm	800mm 1250mm	100x15mm 60x10mm	920mm 1150mm	120x25mm 50x10mm	600mm 400mm
	30x30mm 10x10mm	650mm 1100mm	35x35mm 20x20mm	600mm 780mm	50mm 20mm	600mm 400mm
	50x6mm 30x3mm	600mm 500mm	60x7mm 50x5mm	750mm 500mm	80x40x7mm 40x40x5mm	500mm 400mm
	50x6mm 30x3mm	600mm 500mm	60x7mm 50x5mm	750mm 700mm	80x40x7mm 40x40x5mm	400mm 360mm
	60x40x6mm 30x15x4mm	600mm 900mm	80x45x6mm 65x40x5mm	600mm 550mm	100x50x-6mm 50x40x5mm	600mm 500mm
	60x40x6mm 30x15x4mm	600mm 900mm	80x45x6mm 65x40x5mm	650mm 550mm	100x50x-6mm 50x40x5mm	600mm 500mm
	50x5mm 30x4mm	500mm 500mm	60x5mm 50x5mm	500mm 500mm	70x6mm 40x5mm	500mm 400mm
	50x5mm 30x4mm	500mm 500mm	60x5mm 50x5mm	700mm 700mm	70x6mm 40x5mm	600mm 500mm
	30mm 10mm	650mm 1100mm	35mm 30mm	600mm 650mm	50mm 20mm	600mm 400mm
	50x50x-2.5mm 30x30x-2mm	700mm 800mm	60x60x3mm 40x40x3mm	600mm 500mm	70x70x3mm 30x30x3mm	900mm 500mm
	50x25x-2.5mm 40x20x2mm	800mm 1000mm	70x50x3mm 50x40x3mm	1200mm 800mm	80x40x3mm 50x30x2mm	800mm 500mm

**RR65**

OPTIONAL ROLLERS

Model	RR40	RR50	RR65
Profile	Size	Size	Size
	30x2 mm 35x2mm 40x2mm 45x2mm 50x2mm 55x2mm 60x2mm 65x2mm 70x2mm	30x2mm 35x2mm 40x2mm 45x2mm 50x2mm 55x2mm 60x2mm 65x2mm 70x2mm	3-1/2"X2" (dia. 900mm) 2-1/8"X2" (dia. 500mm) 100X2mm (dia. 1000mm) 60x2mm (dia. 500mm)

Features:

- Steel-Welded Construction Frame
- With Hydraulic Motor
- Mobile Control Panel
- Top Roll Hydraulic Moveable
- One Standard Combination Roller
- Horizontal And Vertical Working Position

* The above specifications are subject to change without prior notice, no liability for mistakes. Machines may be shown with optional equipment.

