



Chester Universal Milling Machine

- 240V Mains Operated
- Ground Column Slide ways
- Variable Speed Horizontal + Vertical
- 3 Axis Digital Readout

Table	
Working Surface	240x1000mm
T-Slots, Number and Size	5/14mm
T-Slots Centres	44mm
Longitudinal Travel	600mm
Cross Travel	230mm
Vertical Travel	360mm
Load Capacity	150kg
Spindle (Vertical)	
Spindle Taper	ISO30
Number of Speeds	Variable 2steps
Speed Range	115-1750rpm
Spindle Centre to Column	210-600mm
Spindle to Table	65-385mm
Quill Travel	120mm
Milling and Drilling Capacity in Steel (S235JR) - Vertical	
End Milling Capacity	25mm
Vertical Milling Capacity	
Tapping Capacity	M16
Drilling Capacity	50mm
Spindle (Horizontal)	
Spindle Taper	ISO30
Number of Speeds	variable 2steps
Speed Range	60-1350rpm
Spindle to Table	0-300mm
Milling and Drilling Capacity in Steel (S235JR) - Horizontal	
End Milling Capacity	100mm
Tapping Capacity	M16
Drilling Capacity	50mm
Feed Rates	
Number of Feeds	Stepless
Longitudinal	Manual
Cross	Manual
Vertical	Manual
Power	
Spindle Drive Motor	1.5kw(2.04hp)
Coolant Motor	0.04kw(0.05hp)
Weight and Dimensions	
Overall Dimensions (L x W x D)	1100x1200x2100mm

STANDARD ACCESSORIES

- ✓ 3-Axis Digital Read Out
- ✓ Coolant Tray
- ✓ Work Lamp
- ✓ Tool Kit
- ✓ Manual & Parts List
- ✓ Table Power Feed
- ✓ Horizontal Arbors

OPTIONAL ACCESSORIES

- ER Collets
- Vice
- Clamp Kit
- Boring Head Set
- Reducing Sleeves
- Universal Dividing Head
- 3 Jaw Chuck for Dividing Head
- Rotary Table
- ...
- ...