



Chester Lathe



- Precision Ground and Hardened Bedways
- Head Stock Gears are Made of High Quality Steel Ground and Hardened

STANDARD ACCESSORIES:

- ✓ 2 Axis Digital Read Out
- ✓ Three Jaw Chuck
- ✓ Four Jaw Chuck
- ✓ Auto Lubrication System
- ✓ Fixed Steady
- ✓ Traveling Steady
- ✓ Thread Chasing Dial
- ✓ Steel Centre
- ✓ Leadscrew Guard
- ✓ Chuck Guard
- ✓ Toolpost Guard
- ✓ LED Work Lamp
- ✓ Coolant System
- ✓ Tools and Tool Box
- ✓ Operation Manual

OPTIONAL ACCESSORIES:

- Face Plate
- Live Centre
- Back Plate
- Indexable Lathe Tools
- Soft Jaws
- Drill Chuck & Arbor
- Quick Change Toolpost

Centre Height	166mm
Swing Over Bed	330mm
Distance between Centres	500mm/750mm/1000mm
Swing Over Cross Slide	198mm
Swing In Gap	476mm
Gap Length in Front of Face Plate	210mm
Cross Slide Travel	170mm
Top Slide Travel	95mm
Bed Width	187mm
Spindle Nose	D1-4
Spindle Bore	51mm
Taper Reduction in Sleeve	MT5
Number of Spindle Speed Ranges	8
Range of Spindle Speeds	70-2000r/min
Quill Diameter	32mm
Quill Travel	100mm
Quill Internal Taper	MT3
Longitudinal Feeds	0.002-0.548"/rev(Imp.) 0.052-0.392mm/rev(Met.)
Cross Feeds	0.007-0.0187"/rev(Imp.) 0.014-0.380mm/rev(Met.)
Metric Threads	0.4-7mm
Imperial Threads	4-56T.P.I
Module Threads	n/a
Diametral Threads	n/a
Pitch of Leadscrew	8T.P.I
Main Motor	1.5kw(2.04hp)
Coolant Pump Motor	0.04kw(0.05hp)
Dimensions	1780/1950x750x1510mm
Net Weight	620kg

* The above specifications are subject to change without prior notice, no liability for mistakes. Machines may be shown with optional equipment.