



Chester CNC Lathe • EDU360



- Suitable for Processing Precision Internal or External Diameter, Face, Taper, Arc and Threading with High Accuracy
- Induction Hardened Bedway
- Spindle is Supported by Precision Bearings
- Suitable for Education Environments



Model	EDU360
Distance between Centres	500mm/750mm/1000mm
Swing over Bed	360mm
Swing over Carriage	150mm
Spindle Bore	51mm
Spindle Speed Range (Variable)	100-2500r/min
Feed Motor Torque (X/Z)	4N.M/6N.M
X Rapid Traverse	6m/min
Z Rapid Traverse	6m/min
Max.Travel of X Axis	170mm
Max.Travel of Z Axis	400mm/650mm/900mm
Motor Power	3kw (4hp)
Electrical Tool post	4 stations
Max.Tool Size	16x16mm
Min Input Unit	0.001mm
Repeatability Accuracy(X/Z)	0.016mm
Barrel Travel of Tail stock	130mm
Barrel Taper of Tail stock	MT3
Dimensions	2100x1200x1850mm 2350x1200x1850mm 2600x1200x1850mm
Weight	1500/1600/1700kg

Standard Accessories:

- ✓ Siemens/Fanuc Controller
- ✓ 3-jaw Chuck
- ✓ Tool Post Wrench
- ✓ Electrical Tool Post (4 Station)
- ✓ Cooling System
- ✓ Manual Lubrication System
- ✓ Working

Optional Accessories:

- 6 or 8 Stations Tool post
- Pneumatic Chuck
- Hydraulic Chuck
- Auto-Lubrication
- Bar Feeder

* The above specifications are subject to change without prior notice, no liability for mistakes. Machines may be shown with optional equipment.

