



## CNC Milling Machine Compact Mill 21



| Model                             | Compact Mill 21 |
|-----------------------------------|-----------------|
| Max. Drilling Dia.                | 20mm            |
| Max. Milling Dia.                 | 20mm            |
| Max. Tapping Dia.                 | M8              |
| Spindle Speed                     | 3000rpm         |
| Spindle Center to Column Distance | 194mm           |
| Spindle Nose to Table Distance    | 215mm           |
| Spindle Taper                     | ER25            |
| T-Slot Size (NXWXD)               | 3/12/40mm       |
| Worktable Size                    | 400x140mm       |
| X Axis Travel                     | 220mm           |
| Y Axis Travel                     | 120mm           |
| Z Axis Travel                     | 200mm           |
| Main Motor Power                  | 1KW             |
| Main Motor Type                   | Servo Motor     |
| Feeding Motor Torque              | 2.0/2.0/3.0 N.m |
| Feeding Motor Type                | Servo Motor     |
| Controller System                 | SIEMENS 808D    |
| Over Size (LXWXH)                 | 1230X770X1800mm |
| N.W                               | 310kgs          |
| G.W                               | 330kgs          |

### Standard Accessories:

- Siemens 808D
- Linear Guideway
- 1.1kw Servo Motor
- Work Light
- Full cover with CE safety clock
- ER Collet (3-16mm)
- Auto Lubrication
- 2.5" Precision Machine Vice
- Tool Probe