

T MILL SUPER X UNIVERSAL MILLING MACHINE



- Constructed with robust Meehanite cast iron for durability
- Slideways hardened and ground for precision
- Table surface hardened for longevity
- Both horizontal and vertical spindles included
- Wide cross slide provides ample table support
- Table swivels 45° left to right for versatile positioning
- Slideways feature tapered gibs for enhanced stability
- X/Y/Z traverse locks ensure secure positioning
- Back gear mechanism delivers maximum torque at lower speeds
- Equipped with a two-axis digital readout system for precise measurement
- Fully geared head for high torque

Model	T MILL SUPER X
Table Size	1270 x 280mm
Table Rotation	+/-45°
Head Swivel	+/-45°
Longitudinal Travel	750mm
Cross Travel	270mm
Vertical Travel	360mm
T Slot No. and Size	5 x 14mm
Distance between spindle axis and column surface	200-600mm
Distance from spindle nose to table surface	65-425mm
Spindle Hole Taper	ISO40
Spindle Travel	120mm
Spindle Speed Range (50hz/60Hz)	115-1750(V)/40-1300(H)
Spindle Motor	0.85/1.5KW(V) 2.2KW(H)
Overall Dimensions (L x W x D)	1640 x 1350 x 2110mm
Net Weight	1250kg

Standard Accessories:

- Pendant Control Box with Integrated 3 Axis DRO
- Interlocked Table Guard
- X Axis Power Feed
- 45° Table Rotation
- Drawbar
- Horizontal Milling Arbor
- Drill Chuck with Taper Shank
- Interlocked Table Guard
- LED Work Light
- Manual Lubrication Pump
- Coolant System
- Chip Tray
- Tool Box
- Manual

Optional Accessories:

- Y Axis Power Feed
- Powered Table Elevation
- Milling Vice
- Angle Milling Vice
- Clamp Kit
- Boring Head Set
- Reducing Sleeves
- Milling Chuck with ER Collets
- Angle Milling Table
- Rotary Table
- Indexing Plate Set for Rotary Table
- Milling Cutter Set
- Drill Set
- Combination Shell End Milling Arbor
- Face Milling Cutter
- Stub Milling Arbor

* The above specifications are subject to change without prior notice, no liability for mistakes. Machines may be shown with optional equipment.