



CPG Line:

Features tilting working-bench from -10° up to 45°; for sharpening HSS steel, TCT insert and bits. Equipped on one side with white sharpening wheel.

CAP Line:

Features heavy duty bench grinder with sharpening tools from 5 to 40 mm diameter. Equipped on one side with white sharpening wheel.

CAPG Line:

Combination of PG + AP lines:
Featuring tilting working-bench from -10° up to 45° to hand sharp HSS steel, TCT insert etc. On the other side sharpening tools from 5 to 40 mm diameter. Equipped on both sides with white sharpening wheels.

Model	Motor	Speed	Wheel Size	Weight	Packing Size
S2-CPG	0.75kW(1hp)	2800rpm	200x25x20mm/ 200x40x20mm	79kg	800 x 710 x 1300mm
S4-CPG	1.5kW(2hp)	1400rpm	250x35x25mm/ 250x50x25mm	99kg	800 x 710 x 1300mm
S6-CPG	2.2kW(3hp)	1400rpm	300x40x30mm/ 300x50x30mm	125kg	800 x 710 x 1300mm
S2-CAP	0.75kW(1hp)	2800rpm	200x25x20mm/ 200x40x20mm	80kg	800 x 710 x 1300mm
S2-CAPG	0.75kW(1hp)	2800rpm	200x40x20mm	85kg	800 x 1200 x 1300mm

* The above specifications are subject to change without prior notice, no liability for mistakes. Machines may be shown with optional equipment.