



- Interlock chuck guard for enhanced safety during operation
- LED lamp for improved visibility of the work area
- Powered spindle feed with depth setting and auto return for efficient drilling operations
- Coolant system to maintain optimal cutting conditions
- Head tilts 45° - 0° - 45° for versatile drilling angles
- Head rotates 360° in the vertical plane for flexible drilling orientations
- Exceptionally quiet gearbox for reduced operational noise
- 4MT hardened spindle for durability and robust performance
- Tapping feature for additional functionality in machining tasks

Model	Lux Plus
Max. drilling capacity (iron/steel)	Ø40/30mm
Spindle taper	MT4
Dimension of base	670 x 470mm (water tank)
Spindle speed (single phase machine)	75-1600rpm (6 steps)
Spindle speed (3 phase machine)	75-3200rpm (12 steps)
Work table size	500 x 460mm
Spindle travel	120mm
Diameter of column	Ø115mm
Max.distance spindle nose to work table	715mm
Max.distance spindle nose to base	1180mm
Motor power	1.1/1.5kW
Machine Dimensions	580 x 680 x 1800mm
Net Weight	305kg
Power supply	240V single Phase / 400V 3 Phase

Standard Accessories:

- MT4 Spindle
- MT4/MT3 Reduction Sleeve
- Coolant Pump
- Auto Tapping Function
- Interlocked Spindle Guard
- Drawbar
- Drill Chuck with Taper Shank
- Double Speed Motor for 3 Phase
- Tool Box
- Manual

Optional Accessories:

- Vice
- Clamp Kit

* The above specifications are subject to change without prior notice, no liability for mistakes. Machines may be shown with optional equipment.