

- Interlocked Spindle Guard
- MT3 Spindle
- Long 120mm Spindle Travel
- Electronic Depth Display providing 3rd Axis Measurement



Standard Accessories:

- MT3 Spindle
- Coolant Pump
- Auto Tapping Function
- Interlocked Spindle Guard
- Drawbar
- Drill Chuck with Taper Shank
- LED Work Light
- Electronic Depth Display providing 3rd Axis Measurement
- Spindle Autofeed
- X Axis Power Feed
- 2 Axis Digital Readout System
- Toolbox
- Manual

Optional Accessories:

- R8 Spindle
- MT4 Spindle
- Y Axis Power Feed
- Single Phase machine without Double Speed Motor
- ER Collet Chuck Set
- Milling Vice
- Clamp Kit
- Boring Head Set
- Reducing Sleeves
- Angle Milling Table
- Rotary Table
- Indexing Plates for Rotary Table
- Milling Cutter Set
- Drill Set
- Face Milling Cutter
- Stub Milling Arbor

Model	Lux Plus
Max. drilling capacity (iron/steel)	45/32mm
Max. end milling capacity	32mm
Spindle taper	MT3
Dimension of base	670 x 470mm
Spindle speed (single phase machine)	75-1600rpm (6 steps)
Spindle speed (3 phase machine)	75-3200rpm (12 steps)
Distance spindle to column	278mm
Work table size	730 x 210mm
Work table travel	490mm(X) 180mm(Y)
Spindle travel	120mm
Diameter of column	115mm
Max.distance spindle nose to work table	610mm
Max.distance spindle nose to base	1180mm
Motor power	1.5kw
Machine Dimensions	1190 x 745 x 1800mm
Net Weight	360kg

* The above specifications are subject to change without prior notice, no liability for mistakes. Machines may be shown with optional equipment.